



Product Table: Chamfer Cutters - Pointed & Flat End
Characteristics: 4 Flutes
Series: 183xx, 8487xx, 8661xx, 8710xx, 8764xx, 8812xx, 8951xx, 9824xx

Product notes:

Due to a varying diameter, an **Effective Cutter Diameter** is needed for Chip Load selection and RPM calculation:
 Effective Cutter Diameter = (Major Diameter + Minor Diameter)/2.
 Or consider the actual diameter along the angle that is engaged with the workpiece.

Depth of Cut is shown as number of Passes with each pass resulting in a descending stepover

Chip Loads are given 3 ways:

Traditional Edge Break of .010"-.015"

Full Chamfer engagement for cutters with angles GREATER than or equal to 25° per side (50° included)

Full Chamfer engagement for cutters with angles LESS than 25° per side (50° included)

Chip Loads within table pertain to machining on one side of workpiece.

For machining on two sides, reduce Chip Loads to 60%-80% depending on contact length and finish

For vertical plunging, reduce Chip Loads to 40%-50% depending on finish

General notes:

All posted speed and feed parameters are suggested starting values that may be increased given optimal setup conditions. Chip loads reflect uncoated cutters and may be increased 10%-20% if coated. For ferrous materials with hardness ≤ 28 Rc, chip loads can be increased 10%-20%.

If you require additional information, Harvey Tool has a team of technical experts available to assist you through even the most challenging applications. Please contact us at **800-645-5609** or **Harveytech@harveyperformance.com**.

WARNING: Cutting tools may shatter under improper use. Government regulations require use of safety glasses and other appropriate safety equipment in the vicinity of use.

MATERIAL	SFM	Hardness: ≤ 28 Rc (≤ 271 HBn)											Depth of Cut Passes				
		Chip Load (IPT) By Effective Cutter Diameter															
		0.015	0.031	0.047	0.062	0.078	0.093	0.125	0.187	0.250	0.312	0.375		0.500			
ALUMINUM ALLOYS																	
Casting (2xx, 5xx, 7xx, 8xx)	750	Edge Break	.00018	.00037	.00056	.00074	.00094	.00112	.00150	.00224	.00300	.00374	.00450	.00600	1		
		Full Chamfer (≥ 25°)	.00015	.00031	.00047	.00062	.00078	.00093	.00125	.00187	.00250	.00312	.00375	.00500	2		
		Full Chamfer (< 25°)	.00011	.00023	.00035	.00047	.00059	.00070	.00094	.00140	.00188	.00234	.00281	.00375	3		
Wrought (1xxx, 2xxx, 3xxx, 5xxx, 6xxx, 7xxx, 8xxx)	1000	Edge Break	.00016	.00033	.00051	.00067	.00084	.00100	.00135	.00202	.00270	.00337	.00405	.00540	1		
Casting - 3%-5% Si (3xx, A3xx, C3xx, 4xx, A4xx, B4xx)	750	Edge Break	.00016	.00033	.00051	.00067	.00084	.00100	.00135	.00202	.00270	.00337	.00405	.00540	1		
Casting - 5%-8% Si (3xx, A3xx, C3xx, 4xx, A4xx, B4xx)	700	Edge Break	.00016	.00033	.00051	.00067	.00084	.00100	.00135	.00202	.00270	.00337	.00405	.00540	1		
Casting - 8%-12% Si (3xx, A3xx, C3xx, 4xx, A4xx, B4xx)	650	Edge Break	.00014	.00028	.00042	.00056	.00070	.00084	.00113	.00168	.00225	.00281	.00338	.00450	2		
Casting - 12%-16% Si (3xx, A3xx, C3xx, 4xx, A4xx, B4xx)	475	Edge Break	.00010	.00020	.00030	.00040	.00050	.00063	.00084	.00126	.00169	.00211	.00253	.00338	3		
Wrought - 5%-8% Si (4xxx)	1000	Edge Break	.00010	.00021	.00032	.00042	.00053	.00063	.00084	.00126	.00169	.00211	.00253	.00338	3		
Wrought - 8%-12% Si (4xxx)	800	Edge Break	.00018	.00037	.00056	.00074	.00094	.00112	.00150	.00224	.00300	.00374	.00450	.00600	1		
MAGNESIUM ALLOYS	1500	Edge Break	.00018	.00037	.00056	.00074	.00094	.00112	.00150	.00224	.00300	.00374	.00450	.00600	1		
		Full Chamfer (≥ 25°)	.00015	.00031	.00047	.00062	.00078	.00093	.00125	.00187	.00250	.00312	.00375	.00500	2		
		Full Chamfer (< 25°)	.00011	.00023	.00035	.00047	.00059	.00070	.00094	.00140	.00188	.00234	.00281	.00375	3		
ZINC ALLOYS	800	Edge Break	.00018	.00037	.00056	.00074	.00094	.00112	.00150	.00224	.00300	.00374	.00450	.00600	1		
		Full Chamfer (≥ 25°)	.00015	.00031	.00047	.00062	.00078	.00093	.00125	.00187	.00250	.00312	.00375	.00500	2		
		Full Chamfer (< 25°)	.00011	.00023	.00035	.00047	.00059	.00070	.00094	.00140	.00188	.00234	.00281	.00375	3		
COPPER ALLOYS																	
High Coppers - 90%+ (C1xxx)	225	Edge Break	.00014	.00030	.00045	.00060	.00075	.00089	.00120	.00180	.00240	.00300	.00360	.00480	1		
Brass (Copper-Zinc alloys, C2xxx, C3xxx, C4xxx, C6400-C69800)	500	Edge Break	.00014	.00030	.00045	.00060	.00075	.00089	.00120	.00180	.00240	.00300	.00360	.00480	1		
Phosphor Bronzes (Copper-Tin alloys, C5xxx)	225	Edge Break	.00014	.00030	.00045	.00060	.00075	.00089	.00120	.00180	.00240	.00300	.00360	.00480	1		
Aluminum Bronzes (Copper-Aluminum alloys, C60600-C64200)	500	Edge Break	.00014	.00030	.00045	.00060	.00075	.00089	.00120	.00180	.00240	.00300	.00360	.00480	1		
Silicon Bronzes (Copper-Silicon alloys, C64700-C68100)	500	Edge Break	.00014	.00030	.00045	.00060	.00075	.00089	.00120	.00180	.00240	.00300	.00360	.00480	1		
Copper-Nickels, Nickel-Silvers (Copper-Nickel alloys, C7xxx)	225	Edge Break	.00014	.00030	.00045	.00060	.00075	.00089	.00120	.00180	.00240	.00300	.00360	.00480	1		
Cast Copper Alloys (C8300-C86200, C86400-C87900, C92200-C95800, C97300-C97800, C99400-C99700)	550	Edge Break	.00009	.00019	.00028	.00037	.00047	.00056	.00075	.00112	.00150	.00187	.00225	.00300	3		

MATERIAL	SFM	Hardness: 29-37 Rc (279-344 HBn)											Depth of Cut Passes			
		Chip Load (IPT) By Effective Cutter Diameter														
		0.015	0.031	0.047	0.062	0.078	0.093	0.125	0.187	0.250	0.312	0.375		0.500		
CARBON STEELS																
Free-Machining/Low Carbon steels, 10xx - 1029 & all 10Lxx, 11xx - 1139 & all 11Lxx, 12xx - 1215 & all 12Lxx	600	Edge Break	.00007	.00014	.00021	.00028	.00035	.00042	.00057	.00085	.00113	.00142	.00170	.00227	1	
		Full Chamfer (≥ 25°)	.00006	.00012	.00018	.00023	.00029	.00035	.00047	.00071	.00095	.00118	.00142	.00189	3	
		Full Chamfer (< 25°)	.00004	.00009	.00013	.00018	.00022	.00026	.00035	.00053	.00071	.00088	.00106	.00142	4	
1030 - 1095, 1140 - 1151, 13xx, 15xx, 20xx, 30xx, 40xx & 4xLxx, 50xx & 5xLxx, 50xx & 50Lxx, 51xx & 51Lxx, 52xx & 52Lxx, 60xx, 80xx, 90xx	200	Edge Break	.00006	.00013	.00019	.00026	.00032	.00039	.00052	.00078	.00104	.00129	.00156	.00207	1	
		Full Chamfer (≥ 25°)	.00005	.00011	.00016	.00021	.00027	.00032	.00043	.00065	.00086	.00108	.00130	.00173	3	
		Full Chamfer (< 25°)	.00004	.00008	.00012	.00016	.00020	.00024	.00032	.00048	.00065	.00081	.00097	.00130	4	
STAINLESS STEELS																
203 EZ, 303 (all types), 416, 416Se, 416 Plus X, 420F, 420FSe, 430F, 430FSe, 440F, 440FSe	450	Edge Break	.00007	.00014	.00021	.00028	.00035	.00042	.00057	.00085	.00113	.00142	.00170	.00227	1	
		Full Chamfer (≥ 25°)	.00006	.00012	.00018	.00023	.00029	.00035	.00047	.00071	.00095	.00118	.00142	.00189	3	
		Full Chamfer (< 25°)	.00004	.00009	.00013	.00018	.00022	.00026	.00035	.00053	.00071	.00088	.00106	.00142	4	
201, 202, 203, 205, 301, 302, 304, 304L, 308, 309, 310, 314, 316, 316L, 317, 321, 329, 330, 347, 348, 385, 403, 405, 409, 410, 413, 420, 429, 430, 434, 436, 442, 446, 501, 502	200	Edge Break	.00006	.00013	.00019	.00026	.00032	.00039	.00052	.00078	.00104	.00129	.00156	.00207	1	
		Full Chamfer (≥ 25°)	.00005	.00011	.00016	.00021	.00027	.00032	.00043	.00065	.00086	.00108	.00130	.00173	3	
		Full Chamfer (< 25°)	.00004	.00008	.00012	.00016	.00020	.00024	.00032	.00048	.00065	.00081	.00097	.00130	4	
414, 431, 440A, 440B, 440C, 13-8, 15-5, 15-7, 17-4, 17-7	150	Edge Break	.00004	.00008	.00012	.00016	.00020	.00024	.00032	.00048	.00065	.00081	.00097	.00130	1	
		Full Chamfer (≥ 25°)	.00003	.00007	.00010	.00013	.00017	.00020	.00027	.00040	.00054	.00067	.00081	.00108	3	
		Full Chamfer (< 25°)	.00002	.00005	.00008	.00010	.00013	.00015	.00020	.00030	.00041	.00051	.00061	.00081	4	
TOOL STEELS																
A, L, O, P, W series	200	Edge Break	.00006	.00013	.00019	.00026	.00032	.00039	.00052	.00078	.00104	.00129	.00156	.00207	1	
		Full Chamfer (≥ 25°)	.00005	.00011	.00016	.00021	.00027	.00032	.00043	.00065	.00086	.00108	.00130	.00173	3	
		Full Chamfer (< 25°)	.00004	.00008	.00012	.00016	.00020	.00024	.00032	.00048	.00065	.00081	.00097	.00130	4	
D, H, M, T, S series	150	Edge Break	.00004	.00008	.00012	.00016	.00020	.00024	.00032	.00048	.00065	.00081	.00097	.00130	1	
		Full Chamfer (≥ 25°)	.00003	.00007	.00010	.00013	.00017	.00020	.00027	.00040	.00054	.00067	.00081	.00108	3	
		Full Chamfer (< 25°)	.00002	.00005	.00008	.00010	.00013	.00015	.00020	.00030	.00041	.00051	.00061	.00081	4	
TITANIUM ALLOYS																
	150	Edge Break	.00004	.00008	.00012	.00016	.00020	.00024	.00032	.00048	.00065	.00081	.00097	.00130	1	
		Full Chamfer (≥ 25°)	.00003	.00007	.00010	.00013	.00017	.00020	.00027	.00040	.00054	.00067	.00081	.00108	3	
		Full Chamfer (< 25°)	.00002	.00005	.00008	.00010	.00013	.00015	.00020	.00030	.00041	.00051	.00061	.00081	4	
HIGH TEMP ALLOYS																
Inconel, Hastelloy, Waspalloy, Monel, Nimonic, Haynes, Discoloy, Incoloy	70	Edge Break	.00004	.00008	.00012	.00016	.00020	.00024	.00032	.00048	.00065	.00081	.00097	.00130	1	
		Full Chamfer (≥ 25°)	.00003	.00007	.00010	.00013	.00017	.00020	.00027	.00040	.00054	.00067	.00081	.00108	3	
		Full Chamfer (< 25°)	.00002	.00005	.00008	.00010	.00013	.00015	.00020	.00030	.00041	.00051	.00061	.00081	4	

MATERIAL	SFM	Hardness: 38-45 Rc (353-421 HBn)											Depth of Cut Passes		
		Chip Load (IPT) By Effective Cutter Diameter													
		0.015	0.031	0.047	0.062	0.078	0.093	0.125	0.187	0.250	0.312	0.375		0.500	
		Edge Break	.00006	.00013	.00019	.00026	.00032	.00039	.00052	.00078	.00104	.00129	.00156	.00207	1
		Full Chamfer (≥ 25°)	.00005	.00011	.00016	.00021	.00027	.00032	.00043	.00065	.00086	.00108	.00130	.00173	4
		Full Chamfer (< 25°)													